
There are no translations available.





LENGTHS (mm)

L1 Wheelbase	4 490
L5 Front overhang	1 370
L6 Rear overhang	1 500
L7 Rear chassis overhang	

2 340

L11 Total length

9 700

L13 Distance between front axle and superstructure

900

L14 Distance from twin axle center to the superstructure center of gravity max / min.

650/510

L16 Superstructure maximum length

7 530

WIDTHS (mm)

B1 Cabin width

2 300

B2 Width over rear wheels

2 460

B3 Overall width

2 500

B4 Width of chassis frame front

1 800

B7 Min. turning circle diameter (m)

16,0

B8 Min. turning clearence circle diameter (m)

17,8

HEIGHTS (mm)

H1 Total height over cabin, unloaded

3 110

H2 Total height over cabin, loaded

3 050

H3 Chassis height, unloaded

1 400

H4 Chassis height, loaded

1 350

H11 Ground clearence, front

300

H12 Ground clearence, rear

330

H20 Max. lift up of the rear wheel

115

WEIGHTS (kg)

G1 Permissible weight on axle 1	7 500
G2 Permissible weight on axle 2	9 500

G3 Permissible weight on axle 3	9 500
G5 Total permissible weight	26 000
G6 Chassis truck net weight	10 500
G7 Chassis truck weight on front axle	5 500
G8 Chassis truck weight on rear axles	5 000
G9 Chassis truck carrying capacity	15 500
G12 Gross combination weight	-

PERFORMANCES

Maximum speed (km/h)	87
Maximum climbing ability (%)	28