



2 075

L11 Total length

8 785

L13 Distance between front axle and superstructure

800

L14/L15 Distance from twin axle center to the superstructure center of gravity max / min.

375/325

L19 Total permissible length of superstructure

6 250

**WIDTHS (mm)**

B1 Cabin width

2 300

B2 Width over rear wheels

2 460

B3 Overall width

2 500

B4 Width of chassis frame front

942

B5 Width of chassis frame rear

762

B6 Min. turning circle diameter (m)

16,00

B7 Min. turning clearance circle diameter (m)

17,80

**HEIGHTS (mm)**

H1 Total height over cabin, unloaded

3 110

H2 Total height over cabin, loaded

3 050

H3 Chassis frame height, unloaded

995

H4 Chassis frame height, loaded

960

H11 Ground clearance, front

320

H12 Ground clearance, rear

330

**WEIGHTS (kg)**

G1 Permissible weight on axle 1

6 500

G2 Permissible weight on axle 2	8 000
G3 Permissible weight on axle 3	8 000
G5 Total permissible weight	22 000
G6 Chassis truck net weight	9 600
G7 Chassis truck weight on front axle	5 100
G8 Chassis truck weight on rear axles	4 400
G9 Chassis truck carrying capacity	12 400
G12 Gross combination weight	-

## PERFORMANCES

Maximum kinematic speed (km/h)	97
Maximum ASR limited speed (km/h)	85
Maximum climbing ability (%)	30