There are no translations available.



LENGTHS (mm)

L1 Wheelbase between axel 1 and 2

3 840

L2 Wheelbase between axel 2 and 3

1 370

L5 Front overhang

1 700

L6 Rear overhang

1 090

L7 Rear chassis overhang

725

L11 Total length

8 000

L13 Distance between front axle and superstructure

1 700

L15 Minim level of superstructure mass point

520

L16 Superstructure length

4 560

WIDTHS (mm)

B1 Cabin width

2 300

B2 Width over rear wheels

2 460

B3 Overall width

2 500

B4 Width of chassis frame front

946

B5 Width of chassis frame rear

766

B7 Min. turning circle diameter (m)

20,90

B8 Min. turning clearence circle diameter (m)

22,10

HEIGHTS (mm)

H1 Total height over cabin, unloaded

3 430

H2 Total height over cabin, loaded

3 370

H3 Chassis height, unloaded

1 480

H4 Chassis height, loaded

1 440

H11 Ground clearence, front

330

H12 Ground clearence, rear

330

WEIGHTS (kg)

G1 Permissible weight on front axle	7 500
G2 Permissible weight on axle 2 and 3	2x9 500
G5 Total permissible weight	26 000
G6 Chassis truck net weight (aprox)	13 120
G7 Chassis truck weight on axle 1	6 230
G8 Chassis truck weight on rear axles	6 890
G12 Chassis truck carrying capacity	12 880
G13 Towing weight	40 000
G14 Total weight solo, technical permissible	33 000
G15 Gross combination weight	90 000

PERFORMANCES

Maximum kinematic speed (km/h)	86
Maximum climbing ability (%)	30